DOCUMENT 1/1

DOCUMENT

NUMBER

@: unavailable



1. <u>JP,03-216223,A</u> (1991)

BACK

MENU

HELP !

NEXT

SEARCH

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

03-216223 24.09.1991

(43)Date of publication of application:

(51)Int.Cl. B21D 28/02

B21D 28/00

(21)Application number:

(22)Date of filing:

02-009181 (71)

Applicant : **18.01.1990** (72)Inventor :

CABLE LTD KAWAMURA TOSHIO

HITACHI


ENDO HIROHISA SUZUMURA TAKASHI

(54) PRESS PUNCHING METHOD


the residual strain of a formed part after it is punched and to improve its accuracy by giving a force by vibration acceleration in a punching direction for punching.

CONSTITUTION: A blank (d) is held by a die (e) and a stripper

(57)Abstract: PURPOSE: To reduce



(c) and punched by a punch (a). In this time, vibration accelerating force is synthesized by a vibrating device (f) and given to the blank



(d). One shot of punching force itself is not given to the blank (d) and forces divided into fine displacements are given at plural times to punch the blank. Consequently, the residual strain of the formed part is reduced after it is punched. The punched section is improved in accuracy, too.